

Material Safety Data Sheet A4011 – Fast Liquid

1. Product and Company Identification		
Product Name:	Fast Liquid	
Article Code:	A4011	
Manufacturer:	CNC International BV	
	Bronsstraat 17	
	6031 TS Nederweert – The Netherlands	
Emergence Telephone Numbers:	+31 88 5155850	
2. Hazards Identification		

2.1. Classification of the substance or mixture

Classification under CLP: Most important adverse effects :	Flam. Liquid 2. H225 Highly Flammable liquid and vapour Skin Irrit. 2. H315 Causes skin irritation Eye Irrit. 2. H319 Causes serious eye irritation Skin Sens. 1 H317 May cause an allergic skin reaction STOT SE 3 H355 May cause respiratory irritation Highly flammable. Irritating to eyes, respiratory system and skin. May cause sensitization by skin contact.	
2.2 Label elements		
Label elements under CLP: Hazard statements:	H225: Highly flammable liquid and vapour. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H335: May cause respiratory irritation.	
Signal words: Hazard Pictograms:	Danger GHS02: Flam GHS07: Exclamation Mark	
Precautionary statements:	 P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read carefully and follow all instructions. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261: Avoid breathing dust/fume/gas/mist/vapours/spray. P280: Wear protective gloves/protective clothing/eye protection/face protection. P303+361+353: IF ON SKIN (or hair); Remove immediately all contaminated clothing. Rinse skin with. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. 	

Revised Date: 14-8-2023 / Replaces Date: 23-06-2023



Material Safety Data Sheet

A4011 – Fast Liquid

Page 2

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

PBT:

This product is not identified as a PBT substance

3. Composition / Information on Ingredients

3.2 Mixtures Hazardous Ingredients:

Ethyl Methacrylate

EINECS	CAS	CLP Classification	Percent
202-597-5	97-63-2	Flam. Liq . 2: H225; Skin Irrit. 2: H315; Skin Sens. 1 : H317; Eye Irrit. 2: H319; STOT SE3: H335;	70-90%

Hydroxypropyl methacrylate

EINECS	CAS	CLP Classification	Percent
248-666-3	27813-02-1	Eye Irrit. 2: H319; Skin Sens. 1 : H317	10-25%

PEG-4 Dimethacrylate

EINECS	CAS	CLP Classification	Percent
203-653-1	109-17-1	Eye Irrit. 2: H319; Skin Irrit. 2: H315;	1-10%

Dimethyltolylamine

EINECS	CAS	CLP Classification	Percent
-	29256-93-7	Eye Dam. 1, H318; Acute Tox. 4: H302; Skin Irrit. 2: H315; Skin Sens. 1 : H317; Aquatic Chronic 3: H412	<1%
		Skill Sells. 1. HS17, Aquatic Chronic S. H412	

4. First Aid Measures

4.1. Description of first aid measures

Skin contact: Immediately flush skin with plenty of water.

Inhalation:	Remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to- mouth. If breathing is difficult, give oxygen. Get medical attention.
Ingestion:	If swallowed, do NOT induced vomiting. Have victim drink 8-10 ounces of water to dilute material in stomach. Get medical attention immediately. Never give anything by mouth to an unconscious person.
Eye Contact:	In case of contact, Immediately wash the eyes with plenty of water for at least 15 min. holding the eye open. Obtain medical attention urgently.

4.2 Most important symptoms and effects, both acute and delayed

Skin contact: An itchy rash may occur at the site of contact.



Material Safety Data SheetA4011 – Fast LiquidPage 3Eye contact:There may be irritation and pain. The vision may become blurred.Ingestion:The casualty may appear intoxicated.Inhalation:There may be irritation of the throat with a feeling of tightness in the chest.5. Fire Fighting Measures5.1. Extinguishing mediaExtinguishing media:Alcohol resistant foam. Dry chemical powder.

toxic fumes of carbon dioxide/carbon monoxide.

5.2. Special hazards arising from the substance or mixture **Exposure hazards:** Highly flammable. Forms explosive air-vapour mixture. In combustion emits

5.3. Advice for fire-fighters Advice for fire-fighters:

As in any fire, wear self-contained positive-pressure breathing apparatus and full protective gear. Containers can build up pressure if exposed to heat (fire). Cool with water spray.

6. Accidental Release Measures

6.1. Step to be taken in case material is released or spilled

Remove all sources of ignition and ventilate area. Wear appropriate safety equipment as listed in Section 8. Absorb on inert material, then place in a chemical waste container. After removal, flush contaminated area with water and collect for disposal. Clean up spills immediately. Obey relevant local, state, and federal law regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.

7. Handling and Storage

7.1. Precautions for safe handling

Handling requirements:	Keep away from heat. Keep away from sparks, flames and other sources of ignition. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Store in well-ventilated area. Use explosion-proof equipment. Wash thoroughly after handling. Follow all MSDS/label precautions even after the container is emptied because it may retain product residues. Wash thoroughly after handling.
Other Precautions:	Avoid ignition sources or excessive temperatures. Heat can induce polymerization with rapid release of energy. Closed containers may rupture explosively. Spontaneous polymerization may occur with prolonged aging.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions:Store in cool, well ventilated, dry area. Keep container tightly closed. Maintain air
space inside storage containers.

8. Exposure Controls / Personal Protection



Material Safety Data Sl 8.1. Control parameters	neet A4011 – Fast Liquid	Page 4
Workplace exposure limits:	Not applicable.	
8.2. Exposure controls Engineering measures:	Use process enclosures, local exhaust ventilati control airborne exposure. Use explosion-proc	
Respiratory protection:	Wear an appropriate, properly fitted respirate application and handling unless air monitoring below applicable limits. Follow respirator man selection and use.	g demonstrates vapour/mist levels
Ventilation:	Sufficient ventilation must be provided to mai TLV, PEL and LEL limits as listed in Section 8.	ntain airborne concentrations below
Hand protection:	Chemical resistant protective gloves should be Check with glove manufacturer to determine	
Eye protection:	Splash-proof chemical goggles should be worr	1
Skin protection:	Impervious clothing and boots should be worr be provided.	n. Eye bath and safety shower should
Hygenic practices:	Good personal hygiene practices are required These practices include, but are not limited to removed, at the end of each shift or when goi contamination occurs.	, washing when safety equipment is

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form:	Liquid	
Colour:	Colourless	
Odour:	Characteristic	
Boiling Point:	118-119 °C	
Octanol/Water Partitioning Coefficient: n.a.		
Viscocity:	Non-viscous	
Vapour Pressure :	16 hPa	
Density at 20 °C:	0,944 g/cm3	
Flash Point:	18°C	
pH:	N/A	
VOC g/l:	0,02%	
Melting point/rance °C:	Undetermined	

10. Stability and Reactivity

10.1. Reactivity Reactivity:

Stable under recommended transport or storage conditions.



Material Safety Data She 10.2. Chemical stability	et A4011 – Fast Liquid	Page 5	
Chemical stability:	Stable under normal conditions.		
10.3. Possibility of hazardous rea	actions		
Hazardous reactions:	Hazardous reactions will not occur under i	normal transport or storage conditions.	
<i>10.4. Conditions to avoid</i> Conditions to avoid:	Direct sunlight. Heat. Sources of ignition.	Flames. Light.	
<i>10.5. Incompatible materials</i> Materials to avoid:	Strong acides. Oxidizing agents.		
10.6. Hazardous decomposition products			

Haz. decomp. Products: in combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. Toxicological Information

11.1. Information on toxicological effects

Ethyl Methacrylate

IPR	RAT	LD50	1223	Mg/kg
ORL	MUS	LD50	7836	Mg/kg
ORL	RAT	LD50	14800	Mg/kg

2-Hydroxyethyl Methacrylate

IPR	RAT	LD50	1250	Mg/kg
ORL	MUS	LD50	3275	Mg/kg
ORL	RAT	LD50	5050	Mg/kg

12. Ecological Information

Any reject of this product in the sewer or stream must be avoided.

13. Disposal Considerations

Incinerate in a furnace where permitted under national and local regulations.

14. Transport Information

14.1 UN Number UN number ADR/IMDG/IATA: UN1263

14.2: UN proper shipping nameADR:UN 1263 PaintIMDG, IATA:PAINT



Material Safety Data Shee	A4011 – Fast Liquid	Page 6
14.3 Transport hazard class(es) Transport Class ADR/IMDG/IATA		
<i>14.4: Packing group</i> Packing group ADR/IMDG/IATA:		
14.5 Environmental hazards Environmentally hazardous: N	Marine pollutant: No	
14.6 Special precautions for userTunnel codeDTransport category2Limited Quantities (LQ):5		

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture. Not applicable

16. Other Information

DISCLAIMER

While CNC International BV believes that the data contained herein are accurate and derived from qualified sources, the date are not to be taken as a warranty or representation for which CNC International BV assumes legal responsibility. They are offered solely for your consideration, investigation and verification. Any use of these data information must be determined by the user to be in accordance with applicable Federal, State and local laws regulations.

CNC International BV requires all Customers who receive this Security Data Record to study it carefully in order to be informed of any dangers presented by the product. As far as security is concerned, the Customer should:

- Inform his employees, agents and sub-contractors of information contained in this form.
- Supply one copy of this form to each one of his own Customers for this product.
- Ask for these same Customers to inform in turn their own Employees and Customers.